



NARROW STILE CODELOCK



Narrow stile mechanical Codelock suitable for aluminium doors. An affordable alternative to electronic keypads, electrical strikes, magnetic locks and other systems used on aluminium framed doors.

The narrow stile lock is medium duty, ideal for new or retrofit applications. Designed to be retrofitted to Adams Rite or similar ANSI round cylinder mortice deadlatches. Deadlatches are also available from Codelocks (see reverse for further detail). The locks have a variety of access control functions, allowing the user flexibility on how to manage entry - by key, code or code free entry.



Easy to install



Suitable for aluminium doors



Limited lifetime guarantee*

8,191

Total code combinations

FEATURES

- Full size lever handles with return to door
- Ball shape knob available
- Stubby lever handle available
- Code Free access options
- Suitable for internal and external aluminium doors
- Two models available
- PVD low maintenance finish
- Stainless steel finish
- Neoprene seals included
- Field handed keypad - will fit doors hung on the left or right

LOCK MODELS



CL460 / CL465

Front and Back Plates

Narrow stile Codelock complete with cams, threaded cylinder and lever handles.



CL470 / CL475

Front and Back Plates

Narrow stile Codelock complete with cams, Euro profile cylinder and lever handles.

ADDITIONAL FEATURES

Latch Options

25mm (1") and 29mm (1¹/₈") backset latches available on request (sold separately).

Deadlatch Options

P460 DL25 RH / LH:


Deadlatch (round screw in cylinder type only), complete with flat and radius silver grey faceplates - backset 25mm (1") right hand and left hand available.

Compatible: 460/465/470/475

P460 DL29 RH / LH:

Deadlatch (round screw in cylinder type only), complete with flat and radius silver grey faceplates - backset 29mm (1¹/₈") right hand and left hand available.

Compatible: 460/465/470/475



Code Change Method

Requires removal of the lock from the door. The code can be changed by repositioning the tumblers in the code chamber. Locks are supplied with a random code commencing with the 'C' clear button.


Code Free Access

The CL465 and CL475 models provide a Code Free Access mode. These models feature a black dot on the 'Y' button. When the 'Y' button is pressed along with a correct code input, the lever will retract the latch freely until disabled.

TECHNICAL SPECIFICATIONS

FEATURE	DESCRIPTION
Spindle Type	Two part 6mm (1/4") spring loaded spindle
Latch	Two sizes available - sold separately
Handle Options	Lever handle - standard (L) Ball shape knob (B) Stubby lever (SL)
Models	Threaded cylinder and Euro profile cylinder available
Material	Zinc Alloy
Finish	PVD (Physical Vapour Deposition), low maintenance
Finish Colour	Stainless Steel
Non Handed	Locks will fit doors hung on the left or right
Door Thickness	45mm - 55mm (1 ³ / ₄ " - 2 ³ / ₁₆ ")
Door Material	Aluminium
Codes	8,191 non sequential code combinations available
Code Storage	Single Code
Buttons	14 stainless steel buttons
Fitting Options	Vertical only
Suitable For	Internal and external use
Keyed Alike	Locks can be supplied keyed alike on request

PRODUCT DIMENSIONS



Scan to shop!

www.codelocks.com

